




# **bmcs** course

## **Energy Games**


work supply, stored energy, energy dissipation

Rostislav Chudoba  
Abedulgader Baktheer  
Institute of Structural Concrete

*work supply*





# There is even more information hidden in the pull-out curve




How much energy do we have to supply to reach the point A?

# There is even more information hidden in the pull-out curve



# There is even more information hidden in the pull-out curve




How much energy do we have to supply to reach the point A?

Recall the work definition:  
assuming constant force  $\bar{P}$  [N]  
the work needed to displace  
an object to  $w$  [m] is

$$W = \bar{P}w \text{ [Nm]}$$

# There is even more information hidden in the pull-out curve




How much energy do we have to supply to reach the point A?

Recall the work definition assuming constant force  $\bar{P}$  [N] the work needed to displace an object to  $w$  [m] is

$$W = \bar{P}w \text{ [Nm]}$$

# Work supply




**How much energy do we have to supply to reach the point A?**

Recall the work definition assuming constant force  $\bar{P}$  [N] the work needed to displace an object to  $w$  [m] is

$$W = \bar{P}w \text{ [Nm]}$$

**BUT** what if  $P(w) \neq \text{constant}$

# Work supply



**How much energy do we have to supply to reach the point A?**


Recall the work definition assuming constant force  $\bar{P}$  [N] the work needed to displace an object to  $w$  [m] is

$$W = \bar{P}w \text{ [Nm]}$$

**BUT** what if  $P(w) \neq \text{constant}$

**THEN**  $dW = P(w) dw$

# Work supply



How much energy do we have to supply to reach the point A?


$$dW = P(w) dw$$

$$W = \int_0^w P(w) dw$$

$$W = \int_0^w P(w) dw$$

*the battery – stored energy*

# Stored energy




**How much energy can be recovered by unloading?**

It depends ...

Are you asking this for material behavior governed by damage or by plasticity?

$$W = \int_0^w P(w) dw$$

# Stored energy



**How much energy can be recovered by unloading?**

It depends ...


Are you asking this for material behavior governed by damage or by plasticity?

**damage**

$$U_\omega = \frac{1}{2} Pw$$

$$W = \int_0^w P(w) dw \quad U_\omega = \frac{1}{2} Pw$$

# Stored energy



How much energy can be recovered by unloading?

It depends ...

Are you asking this for material behavior governed by damage or by plasticity?

damage

$$U_\omega = \frac{1}{2} P w$$


plasticity

$$U_\pi = \frac{1}{2} P \left( \frac{P}{K_0} \right)$$

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

# Stored energy



How much energy can be recovered by unloading?

It depends ...

Are you asking this for material behavior governed by damage or by plasticity?

damage

plasticity

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$


$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

*the energy release*

# Dissipated energy



How big was the energy leak?

$$\mathcal{W}(t) \rightarrow \boxed{\mathcal{L}} \rightarrow \mathcal{U}(t)$$

$$G(t) = \mathcal{W}(t) - \mathcal{U}(t)$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$


$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

# Dissipated energy



How big was the energy leak?

$$\mathcal{W}(t) \rightarrow \boxed{\mathcal{S}} \rightarrow \mathcal{U}(t)$$

$$G(t) = \mathcal{W}(t) - \mathcal{U}(t)$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$

material behavior, boundary  
conditions, geometry


$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

# Dissipated energy



How big was the energy leak?

$$\mathcal{W}(t) \rightarrow \boxed{\Omega} \rightarrow \mathcal{U}(t)$$

$$G(t) = \underline{\mathcal{W}(t)} - \underline{\mathcal{U}(t)}$$

$$G = \mathcal{W} - \mathcal{U} = \int_0^w P(w) dw - U(w)$$

material behavior, boundary  
conditions, geometry


$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

# Dissipated energy




$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$


*elastic bar*



$$G = ?$$


## Dissipated energy – elastic bar loaded in tension

$$G = W - U = \int_0^w P(w) \, dw - U(w)$$




$$W = \int_0^w P(w) \, dw \quad U_\omega = \frac{1}{2} P w \quad U_\pi = \frac{P^2}{2K_0} \quad G = W - U$$

# Dissipated energy – elastic bar loaded in tension





$$G = W - U = \int_0^w P(w) \, dw - U(w)$$



$$\begin{aligned} \tau &= E \varepsilon && - \text{const. law} \\ P &= A \tau && - \text{equilibrium} \\ \varepsilon &= \frac{w}{L} && - \text{kinematics} \end{aligned}$$

$$W = \int_0^w P(w) \, dw \quad U_\omega = \frac{1}{2} P w \quad U_\pi = \frac{P^2}{2K_0} \quad G = W - U$$

# Dissipated energy – elastic bar loaded in tension



$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$W = \int_0^w \frac{EA}{L} w dw = \frac{EA}{2L} w^2$$

$$\begin{aligned}\tau &= E\varepsilon && -\text{const. law} \\ P &= A\tau && -\text{equilibrium} \\ \varepsilon &= \frac{w}{L} && -\text{kinematics}\end{aligned}$$

$$P = \frac{EA}{L} w$$



$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

# Dissipated energy – elastic bar loaded in tension



$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$W = \int_0^w \frac{EA}{L} w dw = \frac{EA}{2L} w^2$$

$$\begin{aligned}\tau &= E\varepsilon && -\text{const. law} \\ P &= A\tau && -\text{equilibrium} \\ \varepsilon &= \frac{w}{L} && -\text{kinematics}\end{aligned}$$

$$P = \frac{EA}{L} w$$

$$W = \int_0^w P(w) dw \quad U_\omega = \frac{1}{2} P w \quad U_\pi = \frac{P^2}{2K_0} \quad G = W - U$$

# Dissipated energy – elastic bar loaded in tension



$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$W = \int_0^w \frac{EA}{L} w dw = \frac{EA}{2L} w^2$$

$$U = \frac{1}{2} \cdot \frac{EA}{L} w \cdot w$$

$$\begin{aligned}\tau &= E\varepsilon && -\text{const. law} \\ P &= A\tau && -\text{equilibrium} \\ \varepsilon &= \frac{w}{L} && -\text{kinematics}\end{aligned}$$

$$P = \frac{EA}{L} w$$



$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

# Dissipated energy – elastic bar loaded in tension



$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$W = \int_0^w \frac{EA}{L} w dw = \frac{EA}{2L} w^2$$

$$U = \frac{EA}{2L} \bar{w}^2$$

$$G = W - U = 0$$

$$\begin{aligned}\tau &= E\varepsilon && -\text{const. law} \\ P &= A\tau && -\text{equilibrium} \\ \varepsilon &= \frac{w}{L} && -\text{kinematics}\end{aligned}$$

$$P = \frac{EA}{L} w$$

**NO DISSIPATION**



$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

# Dissipated energy – pull-out from rigid matrix



$$G = W - U = \int_0^w P(w) dw - U(w)$$

material behavior, boundary  
conditions, geometry



$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

*elastic bar and frictional interface*




$$G = 0$$

$$G = ?$$

# Dissipated energy – pull-out from rigid matrix

$$G = W - U = \int_0^w P(w) \, dw - U(w)$$





$$W = \int_0^w P(w) \, dw \quad U_\omega = \frac{1}{2} P w \quad U_\pi = \frac{P^2}{2K_0} \quad G = W - U$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

[see Tour 2]

$$G = W - U = \int_0^w P(w) \, dw - U(w)$$




$$W = \int_0^w P(w) \, dw \quad U_\omega = \frac{1}{2} P w \quad U_\pi = \frac{P^2}{2K_0} \quad G = W - U$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) \, dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$W = \int_0^w P(w) \, dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$




$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$

$P$  [N]



$$U(w) = ?$$

How much energy was stored?

How would the pull-out test unload?

Maybe along the initial stiffness?

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$



$$G = W - U$$

$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$P \text{ [N]}$$



$$G = W - U = \int_0^w P(w) \, dw - U(w)$$

$$U(w) = ?$$

How much energy was stored?  
How would the pull-out test unload?  
Maybe along the initial stiffness?

$$K_0 = \frac{\partial P}{\partial w} \Big|_{w=0} = \frac{\sqrt{E_f A_f p \bar{\tau}}}{2\sqrt{w}} \Big|_0 = \infty$$

$$W = \int_0^w P(w) \, dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$


$$G = W - U$$

$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$U(w) = ?$$

How much energy was stored?  
How would the pull-out test unload?  
Maybe along the initial stiffness?

$$K_0 = \frac{\partial P}{\partial w} \Big|_{w=0} = \frac{\sqrt{E_f A_f p \bar{\tau}}}{2\sqrt{w}} \Big|_0 = \infty$$

But then - we would ignore the deformation of the pulled-out bar!  
How much energy does it store?

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$



$$G = W - U$$

$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$U(w) = ?$$

How much energy was stored?

How would the pull-out test unload?

Should we unload to the origin then?

Can we reuse the stored energy derived before for a tensile bar?

$$U = \frac{E_f A_f}{2L} w^2$$

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$



$$G = W - U$$

$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$U(w) = ?$$

How much energy was stored?

How would the pull-out test unload?

Should we unload to the origin then?

Can we reuse the stored energy derived before for a tensile bar?

$$U = \frac{E_f A_f}{2L} w^2$$

NO – as it considered constant strain and stress along the bar

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$



$$G = W - U$$

$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$U(w) = ?$$

How much energy was stored?  
How would the pull-out test unload?

Solution: In case of elastic bar we actually evaluated an integral over energy stored in material points

$$U = \int_{\Omega} \sigma_{\text{el}}(x) \epsilon_{\text{el}}(x) dx$$

$$W = \int_0^w P(w) dw$$

$$U_{\omega} = \frac{1}{2} P w$$



$$U_{\pi} = \frac{P^2}{2K_0}$$

$$G = W - U$$

$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$



$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$U(w) = \int_{\Omega} \sigma_{\text{el}}(x) \varepsilon_{\text{el}}(x) dx$$

We already know these two fields for any value of control pull-out displacement  $w$

They were derived in Tour 2:

$$W = \int_0^w P(w) dw$$

$$U_{\omega} = \frac{1}{2} P w$$

$$U_{\pi} = \frac{P^2}{2K_0}$$

$$G = W - U$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$P [N]$$



$$U(w) = \int_{\Omega} \sigma_{\text{el}}(x) \varepsilon_{\text{el}}(x) dx$$

$$W = \int_0^w P(w) dw$$

$$U_{\omega} = \frac{1}{2} P w$$

$$U_{\pi} = \frac{P^2}{2K_0}$$

$$G = W - U$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix



$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$P [N]$$



$$U(w) = \int_{\Omega} E_f \varepsilon_f^2(x) dx$$



[see Tour 2]

$$W = \int_0^w P(w) dw$$

$$U_{\omega} = \frac{1}{2} P w$$

$$U_{\pi} = \frac{P^2}{2K_0}$$

$$G = W - U$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$



$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$P [N]$$



$$U(w) = \int_{\Omega} E_f \varepsilon_f^2(x) dx$$

$$\varepsilon_f(w, x) = \frac{1}{E_f A_f} (\tau p x + \sqrt{E_f A_f \tau p w})$$



$$W = \int_0^w P(w) dw$$

$$U_{\omega} = \frac{1}{2} P w$$

$$U_{\pi} = \frac{P^2}{2K_0}$$

$$G = W - U$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$



$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$P [N]$$



$$U(w) = \int_{\Omega} E_f \varepsilon_f^2(x) dx$$

$$\varepsilon_f(w, x) = \frac{1}{E_f A_f} (\tau p x + \sqrt{2E_f A_f \tau p w})$$



$$W = \int_0^w P(w) dw$$

$$U_{\omega} = \frac{1}{2} P w$$

$$U_{\pi} = \frac{P^2}{2K_0}$$

$$G = W - U$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$P [N]$$



$$U(w) = \int_{\Omega} E_f \varepsilon_f^2(x) dx$$

$$\varepsilon_f(w, x) = \frac{1}{E_f A_f} (\tau p x + \sqrt{E_f A_f \tau p w})$$

$$U(w) = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$W = \int_0^w P(w) dw$$

$$U_{\omega} = \frac{1}{2} P w$$

$$U_{\pi} = \frac{P^2}{2K_0}$$



$$G = W - U$$

$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) \, dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$\implies G = U$$

$$W = \int_0^w P(w) \, dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$


$$G = W - U$$

$$U = \int_{\Omega_{el}} \sigma(x) \varepsilon(x) \, dx$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$\implies G = U$$

**DISSIPATED = STORED?**

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$


$$U = \int_{\Omega_{\text{el}}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$P [N]$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$\implies G = U$$

**DISSIPATED = STORED!**

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$


$$G = W - U$$

$$U = \int_{\Omega_{el}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$\implies G = U$$

1. How much slip remains after unloading?

2. Dissipation and storage processes spatially separable?

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$



$$G = W - U$$

$$U = \int_{\Omega_{el}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$U = \frac{1}{2} P w_{el}$$

$$w_{el} = \frac{2U}{P}$$

$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$\implies G = U$$

1. How much slip remains after unloading?

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$


$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

$$U = \int_{\Omega_{el}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$



$$G = W - U = \int_0^w P(w) dw - U(w)$$

$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$\implies G = U$$

1. How much slip remains after unloading?

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$


$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$


$$U = \int_{\Omega_{el}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$



$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{1}{2} P w_{el}$$

$$w_{el} = \frac{2U}{P}$$

$$\implies G = U$$

$$w_{el} = \frac{2\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}}{3\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}} \cdot \frac{w^{\frac{3}{2}}}{w^{\frac{1}{2}}}$$

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$



$$G = W - U$$

$$U = \int_{\Omega_{el}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{1}{2} P w_{\text{el}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$w_{\text{el}} = \frac{2U}{P}$$

$$\implies G = U$$

$$w_{\text{el}} = \frac{2\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}}{3\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}} \cdot \frac{w^{\frac{3}{2}}}{w^{\frac{1}{2}}} = \boxed{\frac{2}{3}w}$$

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$



$$G = W - U$$

$$U = \int_{\Omega_{\text{el}}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{1}{2} P w_{\text{el}}$$

$$w_{\text{el}} = \frac{2U}{P}$$

$$\implies G = U$$

$$w_{\text{el}} = \frac{2\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}}{3\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}} \cdot \frac{w^{\frac{3}{2}}}{w^{\frac{1}{2}}} = \frac{2}{3} w$$

**BTW:**  
How would  
you evaluate  
unloading  
stiffness?

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$


$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$


$$U = \int_{\Omega_{\text{el}}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$K = \frac{3\sqrt{2}}{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \frac{1}{\sqrt{w}}$$



$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{1}{2} P w_{\text{el}}$$

$$w_{\text{el}} = \frac{2U}{P}$$

$$w_{\text{el}} = \frac{2\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}}{3\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}} \cdot \frac{w^{\frac{3}{2}}}{w^{\frac{1}{2}}} = \frac{2}{3} w$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$\implies G = U$$

**BTW:**  
How would  
you evaluate  
unloading  
stiffness?

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$


$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$


$$U = \int_{\Omega_{\text{el}}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$K = \frac{3\sqrt{2}}{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \frac{1}{\sqrt{w}}$$



$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$\implies G = U$$

$$w_{el} = \frac{2\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}}{3\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}} \cdot \frac{w^{\frac{3}{2}}}{w^{\frac{1}{2}}} = \frac{2}{3}w$$

**BTW:**  
How would  
you evaluate  
unloading  
stiffness?

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$


$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$


$$U = \int_{\Omega_{el}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$K = \frac{3\sqrt{2}}{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \frac{1}{\sqrt{w}}$$



$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$\implies G = U$$

**BTW:**  
How would  
you evaluate  
unloading  
stiffness?

$$w_{el} = \frac{2\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}}{3\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}} \cdot \frac{w^{\frac{3}{2}}}{w^{\frac{1}{2}}} = \frac{2}{3}w$$

**What?** No damage, Perfect plasticity, but unloading somewhere in-between?

$$W = \int_0^w P(w) dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$



$$G = W - U$$

$$U = \int_{\Omega_{el}} \sigma(x) \varepsilon(x) dx$$

# Dissipated energy – pull-out from rigid matrix

$$P = \sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}} \sqrt{w}$$

$$G = W - U = \int_0^w P(w) dw - U(w)$$



$$W = \frac{2\sqrt{2}}{3} \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$U = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$

$$\implies G = U$$

$$w_{el} = \frac{2\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}}{3\sqrt{2} \cdot \sqrt{E_f A_f p \bar{\tau}}} \cdot \frac{w^{\frac{3}{2}}}{w^{\frac{1}{2}}} = \frac{2}{3}w$$

**2. Dissipation and storage processes spatially separable?**

$$W = \int_0^w P(w) dw$$




$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

$$U = \int_{\Omega_{el}} \sigma(x) \varepsilon(x) dx$$

*separation of domains with energy storage and dissipation*



$$G = 0$$

$$G = U$$

$$G = ?$$

# Dissipated energy → it tends to localize into a small material volume

## Realize:

The example combined two energetic devices  
one fully dissipative device → no energy storage (ideally plastic bond), and  
one non-dissipative device → perfect energy storage (elastic bar)

## Idea:

If it is possible to integrate the stored energy in all material points over the domain  
can we also integrate the released energy over the domain?

## 2. Dissipation and storage processes spatially separable?

$$W = \int_0^w P(w) \, dw \quad U_\omega = \frac{1}{2} P w \quad U_\pi = \frac{P^2}{2K_0} \quad G = W - U \quad U = \int_{\Omega_{el}} \sigma(x) \varepsilon(x) \, dx$$

# Dissipated energy → it tends to localize into a small material volume

## Realize:

The example combined two energetic devices  
one fully dissipative device → no energy storage (ideally plastic bond), and  
one non-dissipative device → perfect energy storage (elastic bar)

## Idea:

If it is possible to integrate the stored energy in all material points over the domain  
can we also integrate the released energy over the domain?

$$G = \int_{\Omega_{\text{diss}}} \tau(s, x) s(x) \, dx$$

## 2. Dissipation and storage processes spatially separable?

$$W = \int_0^w P(w) \, dw \quad U_\omega = \frac{1}{2} P w \quad U_\pi = \frac{P^2}{2K_0} \quad G = W - U \quad U = \int_{\Omega_{\text{el}}} \sigma(x) \varepsilon(x) \, dx$$

# Dissipated energy → it tends to localize into a small material volume

Realize:

The example combined two energetic devices



one fully dissipative device → no energy storage (ideally plastic bond), and

one non-dissipative device → perfect energy storage (elastic bar)

Idea:

If it is possible to integrate the stored energy in all material points over the domain  
can we also integrate the released energy over the domain?

$$G = \int_{\Omega_{\text{diss}}} \tau(s, x) s(x) \, dx$$



2. Dissipation and storage processes spatially separable?

$$W = \int_0^w P(w) \, dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

$$U = \int_{\Omega_{\text{el}}} \sigma(x) \varepsilon(x) \, dx$$

# Dissipated energy → it tends to localize into a small material volume

Realize:

The example combined two energetic devices



one fully dissipative device → no energy storage (ideally plastic bond), and

one non-dissipative device → perfect energy storage (elastic bar)

Idea:

If it is possible to integrate the stored energy in all material points over the domain  
can we also integrate the released energy over the domain?

$$G = \int_{\Omega_{\text{diss}}} \tau(s, x) s(x) \, dx$$



2. Dissipation and storage processes spatially separable?

$$W = \int_0^w P(w) \, dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

$$U = \int_{\Omega_{\text{el}}} \sigma(x) \varepsilon(x) \, dx$$

# Dissipated energy → it tends to localize into a small material volume

Realize:

The example combined two energetic devices

one fully dissipative device → no energy storage (ideally plastic bond), and



one non-dissipative device → perfect energy storage (elastic bar)

Idea:

If it is possible to integrate the stored energy in all material points over the domain  
can we also integrate the released energy over the domain?

$$G = \int_{\Omega_{\text{diss}}} \tau(s, x) s(x) \, dx$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$



2. Dissipation and storage processes spatially separable?

$$W = \int_0^w P(w) \, dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

$$U = \int_{\Omega_{\text{el}}} \sigma(x) \varepsilon(x) \, dx$$

# Dissipated energy → it tends to localize into a small material volume

Realize:

The example combined two energetic devices

one fully dissipative device → no energy storage (ideally plastic bond), and


one non-dissipative device → perfect energy storage (elastic bar)

Idea:

If it is possible to integrate the stored energy in all material points over the domain  
can we also integrate the released energy over the domain?

$$G = \int_{\Omega_{\text{diss}}} \tau(s, x) s(x) \, dx = \int_0^w P(w) \, dw - \int_{\Omega_{\text{el}}} E\varepsilon(x)\varepsilon(x) \, dx$$

$$G = \frac{\sqrt{2}}{3} \cdot \sqrt{E_f A_f p \bar{\tau}} \cdot w^{\frac{3}{2}}$$



2. Dissipation and storage processes spatially separable?

$$W = \int_0^w P(w) \, dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

$$U = \int_{\Omega_{\text{el}}} \sigma(x)\varepsilon(x) \, dx$$

$$G = \int_{\Omega_{\text{diss}}} \tau(s, x)s(x) \, dx$$

# Dissipated energy → it tends to localize into a small material volume

Realize:

The example combined two energetic devices




one fully dissipative device → no energy storage (ideally plastic bond), and

one non-dissipative device → perfect energy storage (elastic bar)

Idea:

If it is possible to integrate the stored energy in all material points over the domain  
can we also integrate the released energy over the domain?

$$G = \int_{\Omega_{\text{diss}}} \tau(s, x) s(x) \, dx = \int_0^w P(w) \, dw - \int_{\Omega_{\text{el}}} E \varepsilon(x) \varepsilon(x) \, dx$$



$$W = \int_0^w P(w) \, dw$$

$$U_\omega = \frac{1}{2} P w$$

$$U_\pi = \frac{P^2}{2K_0}$$

$$G = W - U$$

$$U = \int_{\Omega_{\text{el}}} \sigma(x) \varepsilon(x) \, dx$$

$$G = \int_{\Omega_{\text{diss}}} \tau(s, x) s(x) \, dx$$

$$G = \int_{\Omega_{\text{diss}}} \tau(s, x) s(x) \, dx$$

This is really useful! We can evaluate dissipated energy locally!

If we know where the localization and crack propagation occurs, we can focus just onto this region and ignore the non-dissipative (elastic/unloading) rest of the domain

→ this is the fundamental concept behind methods describing **fracture**

# Dissipated energy → it tends to localize into a small material volume

## Realize:

The example combined two energetic devices  
one fully dissipative device → no energy storage (ideally plastic bond), and  
one non-dissipative device → perfect energy storage (elastic bar)

## Idea:

If it is possible to integrate the stored energy in all material points over the domain  
can we also integrate the released energy over the domain?

$$G = \int_{\Omega_{\text{diss}}} \tau(s, x) s(x) \, dx$$

**This is really useful! We can evaluate dissipated energy locally!**

If we know where the localization and crack propagation occurs, we can focus just  
onto this region and ignore the non-dissipative (elastic) rest of the domain  
→ the fundamental concept behind methods describing **fracture**

$$W = \int_0^w P(w) \, dw \quad U_\omega = \frac{1}{2} P w \quad U_\pi = \frac{P^2}{2K_0} \quad G = W - U \quad U = \int_{\Omega_{\text{el}}} \sigma(x) \varepsilon(x) \, dx \quad G = \int_{\Omega_{\text{diss}}} \tau(s, x) s(x) \, dx$$