



Gradient-Extended Damage Modeling Of Heterogeneous Microstructures Using The Fast Fourier Transforms Method

1. Introduction
2. Material Model Formulation
3. Damage Models
4. Coupling Scheme
5. Numerical Examples
6. Summary

Jaeyong Jung

12, April, 2018

1. Introduction

The Object


- Predict the homogenized mechanical response of a composite by means of the Fast Fourier Transform (FFT)

The Scope

- Isothermal quasi-static process (Helmholtz free energy)
- Large deformation model (Neo-Hookean)
- Matrix material shows isotropic elastic-damage behavior
- Fibers are isotropic elastic

2. Material Model Formulation

2.1 Boundary value problem



Deformation gradient decomposed into its average and fluctuation field

Periodic boundary conditions

- \mathbf{u} periodic
- \mathbf{t} anti-periodic

Field equations

- $\text{Div}(\mathbf{P}(\mathbf{X})) = \mathbf{0} \quad \mathbf{X} \text{ in } \Omega$
- $\mathbf{F}(\mathbf{X}) = \mathbf{F}_0 + \tilde{\mathbf{H}}(\mathbf{X}) \quad \mathbf{X} \text{ in } \Omega$
- $\tilde{\mathbf{H}}(\mathbf{X}) = \frac{\partial \tilde{\mathbf{u}}}{\partial \mathbf{X}} \quad \mathbf{X} \text{ in } \Omega$


Average of deformation gradient

- $\mathbf{F}_0 = \frac{1}{\Omega} \int_{\Omega} \mathbf{F}(\mathbf{X}) dV \quad \mathbf{X} \text{ in } \Omega$
- $\frac{1}{\Omega} \int_{\Omega} \tilde{\mathbf{H}}(\mathbf{X}) dV = \mathbf{0} \quad \mathbf{X} \text{ in } \Omega$


(P. Eisenlohr et al., 2013)

2. Material Model Formulation

2.2 Homogenization technique



Heterogeneous problem



Homogeneous problem

Heterogeneous problem

- $\mathbf{P}(\mathbb{C}(\mathbf{X}), \mathbf{F}(\mathbf{X})) = \mathbf{F}\mathbf{S}(\mathbf{X}) \quad \mathbf{X} \text{ in } \Omega$
- $\text{Div}(\mathbf{P}) = \mathbf{0} \quad \mathbf{X} \text{ in } \Omega$


Homogeneous problem

- $\mathbf{P} = \mathbb{C}^0 : \mathbf{F} + \boldsymbol{\tau}(\mathbf{X}) \quad \mathbf{X} \text{ in } \Omega$
- $\boldsymbol{\tau} = \mathbb{C}^0 : \mathbf{F} - \mathbf{P} \quad \mathbf{X} \text{ in } \Omega$
- $\text{Div}(\mathbb{C}^0 : \mathbf{F}) = -\text{Div}(\boldsymbol{\tau}) \quad \mathbf{X} \text{ in } \Omega$


(P. Eisenlohr et al., 2013)

2. Material Model Formulation

2.3 Lippmann-Schwinger equation & spectral solution scheme



Original RVE



Discretized RVE (64×64)

Lippmann-Schwinger equation

- $\tilde{\mathbf{H}} = -(\mathbf{\Gamma}^0 * \boldsymbol{\tau})(\mathbf{X}) \quad \mathbf{X} \text{ in } \Omega$
- $\mathbf{F} = \mathbf{F}_0 - (\mathbf{\Gamma}^0 * \boldsymbol{\tau}) \quad \mathbf{X} \text{ in } \Omega$

Spectral solution technique

- $\hat{\mathbf{F}}(\xi) = -(\hat{\mathbf{\Gamma}}^0 : \hat{\boldsymbol{\tau}})(\xi) \quad \forall \xi \neq \mathbf{0}$
- $\hat{\mathbf{F}}(\xi) = \mathbf{F}_0 \quad \forall \xi = \mathbf{0}$
- $\mathbf{F}(\mathbf{X}) = \text{FFT}^{-1}(\hat{\mathbf{F}}(\xi))$

(P. Eisenlohr et al., 2013)

2. Material Model Formulation

2.4 Fixed-point scheme for inelastic materials



Initialization

- $\mathbf{F}^0(\mathbf{x}) = \mathbf{F}_0 \quad \forall \mathbf{x} \in \Omega$
- Calculate $\mathbf{P}^0(\mathbf{F}(\mathbf{x}))$ using a constitutive law $\forall \mathbf{x} \in \Omega$

Iterate i+1

- (a) Calculate $\boldsymbol{\tau}^i(\mathbf{x}) = \mathbf{P}^i(\mathbf{x}) - \mathbb{C}^0(\mathbf{x}) : \mathbf{F}(\mathbf{x}) \quad \forall \mathbf{x} \in \Omega$
- (b) $\hat{\boldsymbol{\tau}}^i(\boldsymbol{\xi}) = \text{FFT}(\boldsymbol{\tau}^i(\mathbf{x})) \quad \forall \mathbf{x} \in \Omega$
- (c) $\hat{\mathbf{F}}^{i+1}(\boldsymbol{\xi}) = -\hat{\boldsymbol{\Gamma}}^0(\boldsymbol{\xi}) : \hat{\boldsymbol{\tau}}^i(\boldsymbol{\xi}) \quad \forall \boldsymbol{\xi} \neq \mathbf{0}, \quad \hat{\mathbf{F}}^{i+1}(\mathbf{0}) = \mathbf{F}_0$
- (d) $\mathbf{F}^{i+1} = \text{FFT}^{-1}(\hat{\mathbf{F}}^{i+1}) \quad \forall \mathbf{x} \in \Omega$
- (e) Calculate \mathbf{P}^{i+1} and **inelastic state variables** using material laws $\forall \mathbf{x} \in \Omega$
- (f) Check the convergence criterion: $error = \frac{\sum_{\Omega} \|\mathbf{F}^{i+1} - \mathbf{F}^i\|}{N_x N_y N_z \|\mathbf{F}_0\|}$
 - **If** ($error < tolerance$) **return**
 - **Else** go to step (a)

3. Damage Mechanics



Matrix and fiber–matrix interface cracking in composite materials, R. Talreja, 2016

Continuum damage models

- 2nd law of thermodynamics
- Damage loading criterion
- Scalar damage variables

Defect of local continuum damage models

- Ill-posedness in softening region (N. Triantafyllidis et al, 1986)

Nonlocal damage model

- Gradient-extended damage model (micromorphic approach)
- Micromorphic balance equation
- $D \approx \bar{D}$

(S. Forest, 2009)

3. Damage Mechanics

3.1 Local vs. nonlocal damage models

	Local damage	Nonlocal damage
Helmholtz free energy	$\begin{aligned} &\Psi(\mathbf{C}, D, \xi_d) \\ &= f(D) \left[\frac{\mu}{2} \{\text{tr}\mathbf{C} - 3 - \ln(\det\mathbf{C})\} \right. \\ &\quad \left. + \frac{\Lambda}{4} \{\det\mathbf{C} - 1 - \ln(\det\mathbf{C})\} \right] \\ &\quad + r \left\{ \xi_d + \frac{\exp(-s\xi_d) - 1}{s} \right\} \end{aligned}$	$\begin{aligned} &\Psi(\mathbf{C}, D, \xi_d, \bar{D}, \nabla_0 \bar{D}) \\ &= \Psi_{loc}(\mathbf{C}, D, \xi_d) \\ &\quad + \frac{1}{2} H(D - \bar{D})^2 + \frac{1}{2} A \nabla_0 \bar{D} \cdot \nabla_0 \bar{D} \end{aligned}$
Clausius-Duhem inequality	$-\dot{\Psi} + \mathbf{S} : \dot{\mathbf{E}} \geq 0$	$-\dot{\Psi} + \mathbf{S} : \dot{\mathbf{E}} + a_0 \dot{\bar{D}} + \mathbf{b}_0 \cdot \nabla_0 \dot{\bar{D}} \geq 0$
2 nd Piola-Kirchhoff stress	$\mathbf{S} = 2 \frac{\partial \Psi}{\partial \mathbf{C}} = f(D) \{ \mu (\mathbf{I} - \mathbf{C}^{-1}) + \frac{\Lambda}{2} (\det\mathbf{C} - 1) \mathbf{C}^{-1} \}$	
Dissipation inequality	$Y \dot{D} - q_d \dot{\xi}_d \geq 0$	
Damage function	$f(D) = (1 - D)^2$	


3. Damage Mechanics

3.1 Local vs. nonlocal damage models

	Local damage	Nonlocal damage
Thermodynamic conjugate forces	$Y := -\frac{\partial \Psi}{\partial D}$ $= -f'(D) \left[\frac{\mu}{2} \{\text{tr} \mathbf{C} - 3 - \ln(\det \mathbf{C})\} + \frac{\Lambda}{4} \{\det \mathbf{C} - 1 - \ln(\det \mathbf{C})\} \right]$	$Y := -\frac{\partial \Psi}{\partial D}$ $= Y_{loc} - H(D - \bar{D})$
	$q_d := \frac{\partial \Psi}{\partial \xi_d} = r \{1 - \exp(-s \xi_d)\}$	
Damage loading criterion	$\phi_d = Y - (Y_0 + q_d) \leq 0$	
Evolution equations	$\dot{D} = \dot{\lambda} \frac{\partial \phi_d}{\partial Y} = \dot{\lambda}, \quad \dot{\xi}_d = -\dot{\lambda} \frac{\partial \phi_d}{\partial \xi_d} = \dot{\lambda}$	
KKT conditions	$\dot{\lambda} \geq 0, \quad \phi_d \leq 0, \quad \dot{\lambda} \phi_d = 0$	
Micromorphic balance equation	-	$\bar{D} - \alpha \nabla_0^2 \bar{D} = D, \quad \alpha = \frac{A}{H}$

4. Coupling Scheme

4.1 Algorithm for the nonlocal damage model



Coupling Schemes (Simultaneous Scheme)

4.2 Simultaneous scheme for the nonlocal damage model

Application of the Newton-Raphson method

- $\mathbf{x}_0 = \mathbf{0}$
- $\mathbf{x}_{i+1} = \mathbf{x}_i + \Delta \mathbf{x}_i$
- $\mathbf{r}_{i+1} = \mathbf{r}_i + \left(\frac{d\mathbf{r}}{d\mathbf{x}} \right) \Big|_i \Delta \mathbf{x}_i = \mathbf{0}$
- $\Delta \mathbf{x}_i = - \left(\begin{pmatrix} \frac{\partial \mathbf{r}_1}{\partial \Delta \bar{\mathbf{D}}} & \frac{\partial \mathbf{r}_1}{\partial \Delta \lambda} \\ \frac{\partial \mathbf{r}_2}{\partial \Delta \bar{\mathbf{D}}} & \frac{\partial \mathbf{r}_2}{\partial \Delta \lambda} \end{pmatrix}^{-1} \right) \Big|_i \begin{pmatrix} \mathbf{r}_1 \\ \mathbf{r}_2 \end{pmatrix} \Big|_i$
- Submatrices $\in \mathbb{R}^{(N_x N_y N_z) \times (N_x N_y N_z)}$


Submatrix	Definition
$\frac{\partial \mathbf{r}_1}{\partial \Delta \bar{\mathbf{D}}}$	Approximation of $(\mathbf{I} - \alpha \nabla^2)$ using finite-difference schemes
$\frac{\partial \mathbf{r}_1}{\partial \Delta \lambda}$	$\text{diag}(-1)$
$\frac{\partial \mathbf{r}_2}{\partial \Delta \bar{\mathbf{D}}}$	$\text{diag}(H)$
$\frac{\partial \mathbf{r}_2}{\partial \Delta \lambda}$	$\text{diag}(\frac{\partial \phi}{\partial \Delta \lambda})$

Methods to speed up computation

- Express $\frac{\partial \mathbf{r}_1}{\partial \Delta \bar{\mathbf{D}}}$ in sparse matrix form (CSR)
- Schur complement method
- Conjugate gradient method (SPD matrix)

4. Coupling Scheme

4.2 Simultaneous scheme for the nonlocal damage model



Simultaneous scheme


- Solve multiple equations simultaneously
 - $\bar{D} - \alpha \nabla_0^2 \bar{D} = D$
 - $\phi_d = 0$ (damage loading)
- Newton-Raphson method is applied to both equations

Coupling conditions

- $|\bar{D}(\mathbf{X}) - \alpha \nabla_0^2 \bar{D}(\mathbf{X}) - D(\mathbf{X})| < tolerance$
- $\phi_d \leq tolerance$

5. Numerical Examples

5.1 Single fiber, uniaxial stretch




$$\mathbf{F}_0 = \begin{pmatrix} l_i & 0 & 0 \\ 0 & 1/l_i & 0 \\ 0 & 0 & 1 \end{pmatrix}$$
$$l_i \in [1, 1.3]$$


Symbols	Value	Unit
Λ	5000	MPa
μ	7500	MPa
Y_0	5	MPa
r	50	MPa
s	0.5	-
H	10^4	MPa
α	2.5×10^{-8}	MPa mm ²

5. Numerical Examples

5.1.1 Single, local, uniaxial




Stress-principal stretch curve of uniaxial-stretch simulation




Fractured configurations at principal stretch 1.03

5. Numerical Examples

5.1.2 Single, nonlocal, uniaxial




Stress-principal stretch curve of uniaxial-stretch simulation




Fractured configurations at principal stretch 1.03

5. Numerical Examples

5.1.3 Investigations



Damage nucleation sites (256X256)



F_0 just before crack propagation

Observations on the nucleation

- The damage nucleation happens nearby the fiber
- However, $\text{tr}(\mathbf{C})$ is the largest between fibers (large Y)
- Crack goes across mostly damaged regions


Evaluation of the nonlocal model

- Reasonably predicts damage nucleation
- Consistent crack propagations
- Adhesive elements will make the crack more realistic (Nguyen et al., 2010)

5. Numerical Examples

5.2 Multiple fibers, uniaxial stretch


$$\mathbf{F}_0 = \begin{pmatrix} l_i & 0 & 0 \\ 0 & 1/l_i & 0 \\ 0 & 0 & 1 \end{pmatrix}$$
$$l_i \in [1, 1.2]$$




Symbols	Value	Unit
Λ	5000	MPa
μ	7500	MPa
Y_0	5	MPa
r	50	MPa
s	0.5	-
H	10^4	MPa
α	2.5×10^{-8}	MPa mm ²

5. Numerical Examples

5.2.1 Multiple, local, uniaxial




Stress-principal stretch curve of uniaxial-stretch simulation




Fractured configurations at principal stretch 1.02

5. Numerical Examples

5.2.2 Multiple, nonlocal, uniaxial





Stress-principal stretch curve of uniaxial-stretch simulation



Fractured configurations at principal stretch 1.02

5. Numerical Examples

5.3 Multiple inclusions, shear deformation




$$\mathbf{F}_0 = \begin{pmatrix} 1 & l_i & 0 \\ l_i & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$
$$l_i \in [1, l_f]$$


Symbols	Value	Unit
Λ	5000	MPa
μ	7500	MPa
Y_0	5	MPa
r	50	MPa
s	0.5	-
H	10^4	MPa
α	1.0×10^{-8}	MPa mm ²

5. Numerical Examples

5.3.1 Multiple, local, shear




Stress-principal stretch curve of shear deformation simulation




Fractured configurations at principal stretch 1.02

5. Numerical Examples

5.3.2 Multiple, nonlocal, shear



Stress-principal stretch curve of shear deformation simulation



Fractured configurations at principal stretch 1.02

6. Conclusions

Summary


- Development of the numerical scheme for the prediction of elastic-damage behavior in composite materials
 - Nonlocal damage model shows more convincing results

Suggestions for improvements

- More realistic simulations
 - Adhesive elements bonding matrix and fibers
 - Viscoplastic-damage models
 - Uncertainty quantification of the influence of microvoids (D. A. Vajari)
 - Data-driven modeling and parameter estimation using machine learning
- GPGPU acceleration for calculating FFT and inelasticities
- Phase-field damage modeling
 - Possible crack path doesn't have to be known
- Numerical techniques for healing snap-back can be implemented
 - Artificial viscosity models
 - FEA with arc-length solver

Appendix

Multiscale Modeling



Separation of length scales

- $\epsilon = \frac{l}{L} \ll 1$
- Macroscopic material point = microstructure


Representative Volume Element (RVE)

- Microstructure exhibiting the same physical response
- Domain of simulations

Homogenization of a microstructure. Source: CALTECH, found at <http://www.pellegrino.caltech.edu/multiscale-homogenization-of-viscoelastic-unidirectional-composites/>

Appendix

Large Deformation Kinematic



Displacement of a continuum body, from a reference configuration to the current configuration. Source:

Wikipedia, found at

https://commons.wikimedia.org/wiki/File:Displacement_of_a_continuum.svg

Displacement vector

- $\mathbf{u}(\mathbf{x}) = \mathbf{x} - \mathbf{X}$

Deformation and displacement gradient

- $\mathbf{F}(\mathbf{x}) = \frac{\partial \mathbf{x}}{\partial \mathbf{X}} = \mathbf{H}(\mathbf{x}) + \mathbf{I}$
- $\mathbf{H}(\mathbf{x}) = \frac{\partial \mathbf{u}}{\partial \mathbf{X}}$

Right Cauchy-Green deformation tensor

- $\mathbf{C}(\mathbf{x}) = \mathbf{F}^T \mathbf{F}$

Green-Lagrange strain tensor

- $\mathbf{E}(\mathbf{x}) = \frac{1}{2}(\mathbf{F}^T \mathbf{F} - \mathbf{I}) = \frac{1}{2}(\mathbf{C} - \mathbf{I})$

Appendix

FFT-Based Scheme (Lipp.-Sch. Equation in Fourier Space)

The Formulation of solution technique

	Real space	Fourier space
Deformation gradient	$\mathbf{F}(\mathbf{x}) = \frac{\partial \mathbf{x}}{\partial \mathbf{X}}$	$\hat{F}_{mn}(\xi) = i\hat{u}_m(\xi)\xi_n$
First Piola-Kirchhoff stress	$\mathbf{P} = \mathbb{C}^0(\mathbf{x}) : \mathbf{F} + \boldsymbol{\tau}(\mathbf{x})$	$\hat{P}_{kl}(\xi) = \mathbb{C}_{klmn}^0 \hat{F}_{mn} + \hat{\tau}_{kl}(\xi)$ $\Leftrightarrow i\mathbb{C}_{klmn}^0 \hat{u}_m(\xi)\xi_n + \hat{\tau}_{kl}(\xi)$
Divergence free condition	$\text{Div}(\mathbf{P}) = \mathbf{0}$	$i\hat{P}_{kl}\xi_l = 0$
Displacement	$\mathbf{u}(\mathbf{x})$	$\hat{u}_m(\xi) = i\hat{G}_{mk}^0 \hat{\tau}_{kl}\xi_l$
Deformation gradient	$\mathbf{F} = \mathbf{F}_0 - (\boldsymbol{\Gamma}^0 * \boldsymbol{\tau})$	$\hat{F}_{kl} = -\hat{\Gamma}_{klmn}^0 \hat{\tau}_{mn}$
Green's operator	$\boldsymbol{\Gamma}^0$	$\hat{\Gamma}_{kLmN}^0(\xi) = \frac{\delta_{km}\xi_L\xi_N}{2\mu_0 \xi ^2} - \frac{\Lambda_0\xi_k\xi_L\xi_m\xi_N}{2\mu_0(\Lambda_0 + 2\mu_0) \xi ^4}$
Acoustic tensor	\mathbf{G}^0	$\hat{G}^0(\xi) = \frac{(\Lambda_0 + 2\mu_0) \xi ^2\mathbf{I} - \Lambda_0\xi \otimes \xi}{2\mu_0(\Lambda_0 + 2\mu_0) \xi ^4}$

Appendix

FFT-Based Scheme (Defect of Spectral Differentiation)


Limitation of spectral differentiation

- Spectral differentiation is not accurate when derivatives are discontinuous

Remedy

- Approximate differential operators using finite-difference scheme, A. Vidyasagar
- Use $\xi_{ijk} = [\xi_i, \xi_j, \xi_k] = [\frac{\sin(2\pi i/N_x)}{dx}, \frac{\sin(2\pi j/N_y)}{dy}, \frac{\sin(2\pi k/N_z)}{dz}]$

Example



Appendix

Coupling Schemes

Partitioned approaches

- Solve each numerical model individually in a sequence
 - Solve M.B.E. for \bar{D}
 - D.L.C. for D
- Schemes
 - Staggered scheme
 - Coupling condition is not checked
 - Iteratively staggered scheme
 - Solution procedure continues until coupling condition is fulfilled
 - Coupling conditions
 - $|\bar{D}(\mathbf{X}) - \alpha \nabla_0^2 \bar{D}(\mathbf{X}) - D(\mathbf{X})| < tolerance$
 - $\phi_d \leq tolerance$


Simultaneous scheme

- Solve every numerical model at the same time

Appendix

Coupling Schemes (Partitioned Approaches)

Staggered scheme



Solution techniques

- M.B.E. solved using spectral method
- D.L.C. solved using return-mapping algorithm

Spectral method

- $\nabla_0^2 \bar{D}(\mathbf{X}) = \hat{\bar{D}}(\mathbf{X}) |\xi|^2$
- $\hat{\bar{D}} = \frac{\hat{D}}{1 + \alpha |\xi|^2}$


Possible instability

- Solving (M.B.E. & D.L.C) with \mathbf{F}^{i+1} once is not enough to yield converged solution

Appendix

Coupling Schemes (Partitioned Approaches)

Iteratively staggered scheme



Iteration b.t.w. M.B.E. & D.L.C.

- For a given \mathbf{F}^{i+1} , keep iterating the staggered scheme until coupling conditions are fulfilled

Coupling conditions

- $|\bar{D}(\mathbf{X}) - \alpha \nabla_0^2 \bar{D}(\mathbf{X}) - D(\mathbf{X})| < \text{tolerance}$
- $\phi_d \leq \text{tolerance}$

Appendix

Coupling Schemes (Validations of Implementations)

Validation using a homogeneous problem

- Macroscopic deformation gradient at each loading step

- $$\mathbf{F}_0 = \begin{pmatrix} l_i & 0 & 0 \\ 0 & 1/l_i & 0 \\ 0 & 0 & 1/l_i \end{pmatrix} \quad l_i \in [1, l_f]$$

- Material parameters


Parameters	Symbol	Value	Unit
Lamé's first parameter	Λ	5000	MPa
Lamé's second parameter	μ	7500	MPa
Initial damage threshold	Y_0	5	MPa
Damage parameter	r	50	MPa
Exponential damage parameter	s	0.5	-
Penalty constant	H	10^4	MPa
Internal length scale	α	10^{-6}	MPa mm ²

Appendix

Coupling Schemes (Validations of Implementations)

Results

- Comparison between different implementations of nonlocal damage model



Appendix

Coupling Schemes (Validations of Implementations)

Runtime comparison

